



PRINTED CIRCUIT BOARD AND SOLDERING STRUCTURE
FOR ELECTRONIC PARTS THERETO

BACKGROUND OF THE INVENTION

5

1. Field of the Invention

The present invention relates to a printed circuit board having electric or electronic parts soldered to its circuit patterns.

10 2. Related Art

Electric or electronic apparatuses use printed circuit boards, which have a variety of electric or electronic parts soldered to their circuit patterns. Specifically such circuit patterns are formed by labyrinth-like copper foils and the like, each having electric or electronic parts soldered to lands with their terminals inserted in the
15 terminal holes, which are made in the lands.

Fig.5a 5(a) is a plane-plan view of the a land 51 whereas Fig.5b 5(b) is a sectional view of the a land 51, showing the a terminal 54 of a selected electric or electronic part soldered to the land 51. The land 51 is formed on the rear side (the upper side in Fig.5b) 5(b) of the a substrate 50, and the land 51 has a terminal hole
20 52 made-formed at its center. The land 51 is surrounded by a resist layer 53 of an insulating synthetic resin to prevent solder from attaching to the surrounding area.

The terminal 54 of the electric or electronic part is joined to the land 51 by solder.

As seen from Fig.5b 5(b), the ~~a~~ solder lump 55 adhered both to the land 51 and terminal 54 looks like a cone. Its ~~incline~~ inclined sides are dented, and it is small in volume or quantity compared with ~~semi-sphere~~ a hemisphere. Accordingly the
5 cone-like solder lump 55 can hardly provide a holding strength ~~enough~~ sufficient to assure that the electric or electronic part ~~be~~ is fixedly held on the printed circuit pattern. As a matter of fact, when electric or electronic ~~device~~ devices having such printed circuit boards are transported, some parts are ~~shook to come off~~ shaken loose from their printed circuit patterns. Also, printed circuit boards are influenced by
10 surrounding temperature ~~variation~~ variations or by temperature ~~change~~ changes caused by turning printed circuits on and off, so that some parts come off from their printed circuit patterns.

Therefore, it is necessary to locate small solder lumps for applying additional ~~quantity~~ quantities of solder. This, however, is a tedious and time-consuming work.
15 Small solder lumps are easily overlooked. Also, it may be possible that an additional quantity of solder ~~causes~~ will cause short-circuiting.

In the hope of increasing the solder lump quantity ~~of solder lump~~ on each land JP 2000-91737(A), titled "Printed Circuit Boards and Their Manufacturing Method" (see ~~Fig.6~~ Figs. 6(a) and 6(b)), has proposed use of a land comprising a center
20 circular land and a plurality of second sector lands surrounding the first center land. The printed circuit board has electronic parts or devices borne with their terminals

inserted in the terminal holes of the circular lands. Such a printed circuit board is moved to sweep on the melted solder bath, solder lumps separately built on the circular and sector lands, and then these solder lumps are joined together under the influence of surface tension to provide a large solder lump ~~quantity of solder lump~~.

5 Fig.6a 6(a) is a ~~plane-plan~~ view of one example of such composite land whereas Fig.6b 6(b) is a cross section of the composite land taken along the line 6(b) - 6(b) in Fig.6a 6(a). As shown, ~~the~~ a center circular land 56 has a terminal hole 52 ~~made-formed~~ at its center, and four sector lands 57 surround the first center land 56. The A resist layer 58 of an insulating synthetic resin is laid on the copper foil surface,
10 ~~filing~~ filling the inter-land zones.

Printed circuit boards each having circuit patterns printed on ~~its~~ their opposite surfaces are often used. These circuit patterns are locally connected via copper foils (conductor linings) applied to the inner surfaces of the terminal holes. With this arrangement ~~the~~ heat can be transferred from the front to the rear circuit pattern
15 patterns via the conductor linings of the terminal holes when terminals of selected parts and devices are being soldered to one of the front and rear circuit patterns. Thus, the thermal quantity available for soldering will be lower than that for soldering in a printed circuit board having a circuit pattern on one surface. Division of the land into separate sections proposed in JP2000-91737(A) is not so effective in confining
20 the thermal energy to the limited area for soldering, and hence, in increasing the solder quantities in joining the terminal and the land.

Further, JP8-340172(A), titled "Printed Circuit Boards" has proposed a composite land comprising a center circular land and a plurality of second radial lands projecting from the first center land. The inter-radial land spaces are filled with ~~the~~ a resist layer of insulating synthetic resin, which is laid on the copper foil of the substrate. Therefore, thermal energy is permitted to leak from the composite land contour to the underlying copper foil of the inter-radial land space.

In view of the above, one object of the present invention is to provide a printed circuit board whose soldering structure permits an adequate quantity of solder to be used in soldering the terminal of the electric or electronic part to its circuit pattern, thus assuring that the solder lump be strong enough to fixedly hold the part or device on the circuit pattern. Also, another object of ~~he~~ the present invention is to provide a soldering structure which permits an adequate quantity of solder to be used in soldering the terminal of the electric or electronic part or device to its circuit pattern, thus assuring that the solder lump be strong enough to fixedly hold the part or device on the circuit pattern.

SUMMARY OF THE INVENTION

To attain these objects a printed circuit board including a substrate having circuit patterns printed ~~thereon~~ on first and second surfaces thereof is improved according to the present invention in that it has a plurality of composite lands each comprising a first land having a terminal hole made at its center for inserting the

terminal of a selected electric or electronic part or device, and a plurality of second lands each being contiguous to and extending outwards from the first land, and that ~~the~~, for each of the composite lands, thermal insulating areas contiguous to the contours of are provided radially outwardly of the first lands and circumferentially
5 between adjacents ones of the second lands have no, the thermal insulating areas being constituted by areas of the substrate devoid of a conductive foils-layer, such as copper-foils foil, so as to expose the substrate surface of the printed circuit board. The exposed areas effectively prevent thermal energy from leaking outwards from the ~~contour of the composite land~~ when soldering an electric or electronic part or device
10 to the composite land.

The printed circuit board may further comprise, for each of the composite lands, narrow resist layers formed so as to be arranged along between the exposed composite land and each of the thermal insulating areas ~~and the first and second lands.~~

15 A soldering structure for soldering electric or electronic parts to the circuit pattern of a printed circuit board is improved according to the present invention in that ~~it a substrate~~ has a plurality of composite lands each comprising a first land having a terminal hole made at its center for inserting the terminal of a selected electric or electronic part or device, and a plurality of second lands each being contiguous to
20 and extending outwards from the first land, ~~the~~ thermal insulating areas contiguous to ~~the contours of the first and second lands having no conductive foils~~ being devoid of a

conductive layer, such as copper foils-foil, so to expose the substrate surface of the
printed circuit board, whereby the. For at least one of the composite lands, a solder
lump joining is formed on the first land for securing the terminal of the part or device
to the first land and its adjoining second lands ~~may be.~~ The solder lump is shaped
5 into a ribbed conical form having the terminal at its center and its outer ribs integrally
connected to and projecting from the cone.

The soldering structure according to the present invention has
substrate-exposed zones having no thermally conductive foils contiguous to the first
and second lands, thus preventing leakage of thermal energy from the first and
10 second lands. Thus, sufficient quantities of thermal energy can be confined to the
limited area to assure ~~the~~ reliable soldering. Still advantageously, the ridged
cone-like shape is useful in building up the solder lump to be sufficiently strong
~~enough~~ to assure that the terminal of the part or device ~~be~~ is fixedly gripped; the
terminal can be fixedly supported by the surrounding cone-like solder lump and ridge
15 lumps as a whole. This soldering structure requires a minimum quantity of solder
material.

Other objects and advantages of the present invention will be understood from
the following description of some preferred embodiments of the present invention,
which are shown in the accompanying drawings.

20

BRIEF DESCRIPTION OF THE DRAWING DRAWINGS

Fig.4a 1(a) is a ~~plane-plan~~ view of a composite land according to a first embodiment of the present invention; and Fig.4b 1(b) is a sectional view of the composite land taken along the line "1(b)"-"1(b)" in Fig.4a 1(a);

Fig.2a 2(a) is a ~~plane-plan~~ view showing how the soldering lump is built on
5 the composite land of Fig.4 1(a); and Fig.2b 2(b) is a sectional view taken along the line "2(b)"-"2(b)" in Fig.2a 2(a), showing the surrounding cone-like solder lump and ridge lumps;

Fig. 3 is a ~~plane-plan~~ view of a composite land according to a second embodiment of the present invention;

10 Fig. 4 is a ~~plane-plan~~ view of a composite land according to a third embodiment of the present invention;

Fig.5a 5(a) is a ~~plane-plan~~ view showing a conventional circular land; and Fig.5b 5(b) is a sectional view of the circular land taken along the line "5(b)"-"5(b)" in Fig.2a 2(a), showing the cone-like solder lump; and

15 Fig.6a 6(a) is a ~~plane-plan~~ view of a conventional composite land; and Fig.6b 6(b) is a sectional view of the composite land taken along the line "6(b)"-"6(b)".

DETAILED DESCRIPTION OF PREFERRED ~~EMBODIMENT~~ EMBODIMENTS

Referring to ~~Fig.1~~ Figs. 1(a) and 1(b), a printed circuit board has circuit
20 patterns printed on its substrate 1. As shown, a ~~selected-first~~ circular land 3 has a through hole 2 to insert the terminal of a selected electric or electronic part or device,

and four second radial lands 4 are contiguous to the first circular land 3, extending outwards therefrom. The substrate 1 has circuit patterns 6 printed on its opposite sides, and electric or electronic parts or devices are mounted and ~~jointed~~ joined to the composite lands with their terminals inserted in the terminal holes 2 and soldered to
5 the composite lands.

The composite land of copper foil is connected to the underlying circuit pattern 6 on the rear side via the conductor layer 5, which is applied to the inner circumference of the terminal hole 2, as seen from Fig.4b 1(b). A selected part or device is mounted on the rear side of the substrate 1 with its terminal inserted into the
10 terminal hole 2.

As seen from Fig.4a 1(a), the surface of the printed circuit board is locally exposed by removing conductive foils such as copper foils from the areas 8, which are contiguous to the contours of the first and second lands 3 and 4. Also, narrow resist layers 7 are formed between the exposed areas 8 and the first and second
15 lands 2-3 and 3-4.

When soldering the terminal of the part or device to the composite land 2, 3, 4, the thermal energy applied to the composite land is partly allowed to leak to the underlying circuit pattern 6 via the conductor layer 5 of the terminal hole 2. To compensate for the inevitable leak of thermal energy to the underlying circuit pattern
20 6, the exposed areas 8 ~~prevents~~ prevent thermal energy from leaking outwards from the first and second land contours on the front side of the printed circuit board.

Referring to ~~Fig.2~~ Figs. 2(a) and 2(b), the solder lump built up on the composite land is composed of a circular cone-like lump 10 and four radial ridge lumps 9. The ridged cone-like shape has the effect of significantly increasing the strength with which the terminal of the part or device is fixedly held on the circuit pattern. The ridged cone-like lump is smaller in volume than the ~~semi-spherical~~ hemispherical shape whose base is equal to the circular contour drawn by connecting the outer ends of the four radial ridges 9, and accordingly the solder material of the ridged cone-like lump is small in quantity, compared with the ~~semi-spherical~~ hemispherical lump. In spite of this, the ridged cone-like shape can provide comparable holding strength.

Referring to Fig.3, another example of a composite land is composed of a first land 3 having a terminal hole 2 ~~made-formed~~ at its center, and opposite second lands 4a and 4b contiguous to the first land 3, and extending outwards therefrom. Two sectors 8 are formed by removing the underlying copper foils to expose the surface of the substrate 1.

Referring to Fig.4, still another example of a composite land is composed of a first land 3 having a terminal hole 2 ~~made-formed~~ at its center, and four second radial lands 4 contiguous to the first land 3, and extending outwards therefrom. Four five-sided areas 8 each having four straight sides and one curved side are formed by removing the underlying copper foils to expose the surface of the substrate 1.

As may be understood from the above, the composite land is encircled with

thermal insulating zones, which are provided by removing the copper or conductive metal layer from the selected patches, thus exposing the underlying substrate surface.

This effectively prevents thermal energy from leaking outwards from the composite land contour in soldering the terminal of an electric or electronic part or device to the

5 composite land. The resultant ridged cone-like solder lump has an increased strength to hold the terminal in the terminal hole in spite of a relatively small solder quantity used.

ABSTRACT OF THE DISCLOSURE

Disclosed is an improved A printed circuit board having circuit patterns printed thereon. It has a plurality of composite lands each including a first land having a terminal hole ~~made~~ formed at its center for inserting the terminal of a selected electric or electronic part or device, and a plurality of second lands each being contiguous to and extending outwards from the first land. The areas contiguous to the contours of the first and second lands have no conductive foils, such as copper foils ~~to expose,~~ thereon such that the substrate surface of the printed circuit board is exposed in these areas. The exposed areas are effective to confine the thermal energy in the limited areas for soldering. And the composite land shape defines a ridged ~~cone-like~~ cone-like solder lump, which can fixedly grip the terminal of the part or device.